
















**Functionality in a wide range of applications:
We offer a solution for every requirement.**

www.wago.com/relays-and-optocouplers

Series	Input Nominal Voltage	Limiting Continuous Current						AU					ANSI/ISA		Item Number														
2042 Series (10.4 ... 26 mm wide)																													
	24 VDC	6 A													2042-3004														
		8 A													2042-3014														
		5 A													2042-3024														
		10 A													2042-3034														
		8 A													2042-3044														
		6 A	-40 ... +70 °C	1												2042-3054													
	24 ... 230 V AC/DC	8 A		1	1											2042-3064													
		5 A		1	3											2042-3074													
		5 A		2	2											2042-3084													
		3 A			1											2042-3809													
		5 A			2											2042-3819													
		3 A	-40 ... +50 °C	4												2042-3829													
		4 A				1										2042-3839													
		5 A	-40 ... +70 °C			2										2042-3849													
		6 A		1												2042-3859													
		5 A		1	1											2042-3869													
		3 A	-40 ... +50 °C	1	3											2042-3879													
		3 A		2	2											2042-3889													
857 Series Timer Relays (6 mm wide)																													
	24 VDC	6 A	-25 ... +70 °C												857-604														
															857-640														
															857-642														
859 Series (6 mm wide)																													
	5 VDC	-40 ... +50 °C													859-302														
	12 VDC														859-312														
	12 VAC/DC														859-303														
	24 VDC														5 A	-40 ... +70 °C													859-353
																													859-390
																													859-392
																859-398													
	24 VAC/DC		-40 ... +50 °C													859-304													
																859-314													
	36 VDC	3 A														859-354													
															859-386														
	48 VDC	5 A														859-394													
																859-397													
	48 VAC/DC	5 A														859-355													
																859-356													
	60 VAC/DC	3 A														859-393													
																859-399													
	72 VDC	5 A														859-391													
																859-317													
	110 VDC	5 A	-40 ... +70 °C													859-317													
859-317																													
115 VAC/DC	5 A														859-357														
															859-360														
115 VAC	5 A														859-367														
															859-318														
220 VDC	5 A														859-358														
															859-359														
230 VAC/DC	5 A														859-358														
															859-368														

Series	Input Nominal Voltage	Limiting Continuous Current						AU					ANSI/ISA		Item Number	
857 Series (6 mm wide)																
	24 ... 230 V AC/DC		-40 ... +70 °C												857-359	
	12 VDC	6 A													857-369	
	24 VDC														857-303	
	24 VDC														857-304	
	24 VAC/DC	4 A													857-314	
	24 VAC/DC	4 A	-40 ... +60 °C		2x1										857-1330	
	115 VAC/DC														857-354	
	230 VAC/DC	6 A													857-357	
	230 VAC	6 A													857-358	
															857-358/006-000	
															857-368/006-000	
788 Series (15 mm wide)																
	12 VDC	8 A													788-311	
	12 VDC	16 A	-40 ... +70 °C												788-303	
		0.3 A	-40 ... +60 °C													788-353
		8 A	-40 ... +70 °C													788-906*
		8 A	-40 ... +70 °C													788-312
		6 A	-25 ... +70 °C													788-412
		8 A														788-346
		8 A														788-384*
		8 A														788-390
		16 A														788-357
		16 A														788-354
		16 A														788-304
		16 A														788-404
		8 A														788-391
		8 A														788-341
		8 A														788-512
		16 A														788-546
		16 A														788-506
		8 A														788-541
		8 A														788-313
		16 A														788-305
		8 A														788-314
		16 A	-40 ... +70 °C													788-306
		8 A														788-315
		16 A														788-307
		8 A														788-515
		8 A														788-548
		8 A														788-615
	16 A														788-507	
	16 A														788-607	
	8 A														788-543	
	8 A														788-516	
	8 A														788-616	
	16 A														788-549	
	16 A														788-508	
	16 A														788-608	
															788-544	
858 Series (31 mm wide)																
	12 VDC														858-303	
	24 VDC	5 A	-25 ... +70 °C												858-304	
	24 VDC	6 A	-40 ... +70 °C												858-314	
	24 VDC	12 A													858-354	
	24 VDC	12 A													858-355	
	24 VDC	12 A													858-390	
	24 VDC	12 A													858-324	
	24 VAC	5 A	-25 ... +70 °C													858-504
	48 VDC	5 A														858-514
	48 VDC	12 A														858-305
	110 VDC	5 A	-40 ... +55 °C													858-325
	110 VDC	6 A	-40 ... +70 °C													858-307
	110 VDC	12 A	-40 ... +55 °C													858-392
	115 VAC	12 A														858-327
	115 VAC	5 A	-25 ... +70 °C													858-507
	220 VDC	5 A														858-517
	230 VAC	6 A	-40 ... +70 °C													858-308
	230 VAC	12 A	-40 ... +55 °C													858-391
	230 VAC	5 A	-25 ... +70 °C													858-328
	230 VAC	12 A	-40 ... +55 °C													858-508
	12 A														858-518	
															858-528	

*Force-guided contacts